



PROPOSAL



Café Express Gas

FEATURES & BENEFITS

- Impact resistant, see-through Lexan® doors allow customers to see and choose cold beverages.
- Impact-resistant body with UV protective coating
- Independent front suspension with leaf spring and dual hydraulic shocks
- Angled snack shelves for enhanced merchandise presentation
- Consumable ice compartments on both sides
- Standard heavy-duty locks on compartment doors
- Lighter cambros for easier lifting
- Blown-in foam insulation provides superior insulation value and longer ice life.
- NSF rating and ISO 9001 compliance certification
- Industry's Best 2-year Limited Warranty

POWER SOURCE	
Engine	Kawasaki, 4-cycle, OHV, 351 cc, single-cylinder, air-cooled, pressure-lubricated, spin-on oil filter
Horsepower	10.4 hp
Drive Unit	Unitized transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse
STEERING / SUSPENSION	
Steering	Self-adjusting rack and pinion
Front Suspension	Independent leaf spring with dual hydraulic shocks
Rear Suspension	Multi-leaf springs with dual hydraulic shocks
Brakes	Four-wheel, mechanical drum
Park Brake	Foot-Operated
Stabilizer Bar	Anti-sway
BODY / CHASSIS	
Frame Chassis	Aluminum I-beam
Body	ArmorFlex®
Body Color	Matching paint over molded in color
Front/Rear Tires	18 x 8.50-8, 6-ply rated, premium tread
DIMENSIONS	
Overall L x W x H	111.0 x 50.0 x 48.0 in. (281.9 x 127.0 x 121.9 cm)
Wheelbase	77.5 in (196.9 cm)
Ground Clearance	4.5 in (11.4 cm)
Tread	34.5 in/38.6 in (87.6 cm/97.8 cm)
Curb Clearance Circle	296 in (7.5 m)
Maximum Speed	14 mph (22.5 kph)
Turning Radius	120 in (304.8 cm)
Vehicle Warranty	2 year