



PROPOSAL



TransPorter 6 Gas

FEATURES & BENEFITS

- 351 cc gasoline 10.4 hp engine
- Independent front suspension with self-adjusting rack and pinion steering
- Carries up to 6 passengers
- Standard Fixed Rear Seat; Optional Fold Down Rear Seat
- Taillights, brake lights, halogen headlights, and horn
- Rustproof aircraft grade aluminum frame, chassis & optional cargo box
- Max speed of 16 mph (25.7 kph)
- Dual dash compartments
- ArmorFlex® Front Body for fade-resistant color
- Industry's best 2-year limited warranty

POWER SOURCE	
Engine	Kawasaki 4-cycle, OHV, 351 cc, single-cylinder, air-cooled, pressure-lubricated, spin-on oil filter
Horsepower	10.4 hp @ 3,600 rpm, exceeds SAE J1940 Performance Standards
Governor	Automatic ground speed sensing, internally geared-in unitized transaxle
Governed RPM	3050 +/- 30
Ignition	Electronic with electronic limiter
Drive Unit	Unitized transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse
Battery	12-volt, 500 CCA, 105 min. reserve
STEERING / SUSPENSION	
Steering	Self-adjusting rack & pinion
Front Suspension	Independent leaf spring with dual hydraulic shocks
Rear Suspension	Leaf springs with dual hydraulic shocks
Brakes	4-wheel mechanical drum
Park Brake	Foot-operated, multi-lock
Stabilizer Bar	Yes
BODY / CHASSIS	
Frame Chassis	Aluminum I-beam
Front Body	ArmorFlex®
Rear Body	All aluminum
Tires	18 x 6.50-8, 6-ply rated, premium tread
Instrumentation	Electronic fuel gauge/hour meter, low-oil warning light
Trailer Hitch	Standard
Light Package	Standard
DIMENSIONS	
Total Vehicle Capacity	1500 lb (681 kg)
Seating Capacity	6
Overall L x W x H	133.0 x 49.3 x 48.0 in (337.8 x 125.2 x 121.9 cm)
Wheelbase	98.5 in (250.2 cm)
Ground Clearance	4.5 in (11.4 cm)
Fuel Tank Capacity	6 gallons (22.7L)
Tread (Front/Rear)	34.5 in/38.6 in (87.6 cm/97.8 cm)
Dry Weight	842 lb (382.3 kg)
Outside Radius Circle	24.7 ft (7.5 m) dia
Turning Radius	12 ft (3.7 m)
Intersecting Aisle Radius	7.5 ft (228.6 cm)
Speed Range	14-16 mph (22.5-25.7 kph)
Vehicle Warranty	2-year limited