



PROPOSAL



Carryall 242 Gas

FEATURES & BENEFITS

- Rustproof, aircraft-grade aluminum chassis
- Roto-molded plastic, tilt cargo box with 300 lb (136.1 kg) bed load capacity
- 20" all-terrain tires
- Pedal-start conserves fuel
- Fits in full-size pickup truck bed
- Automotive painted finish over impact-resistant ABS front and ArmorFlex rear body
- Headlights, sport steering wheel, dual cupholders, and passenger-side dash pocket
- Tightest turning diameter in its class

POWER SOURCE

Engine	Kawasaki 4-cycle, OHV, 351 cc, single-cylinder, air-cooled, pressure-lubricated, spin-on oil filter
Horsepower	10.4 hp (7.8 kW) @ 3600 rpm per SAE J1349
Drive Unit	Unitized transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse
Batteries	12-volt, 500 cca, 105 min reserve
Key- or Pedal-Start	Pedal

STEERING / SUSPENSION

Steering	Self-adjusting rack and pinion
Front Suspension	Independent leaf spring with dual hydraulic shocks
Rear Suspension	Leaf springs w/dual hydraulic shocks
Brakes	Self-adjusting, rear-wheel, mechanical drum
Park Brake	Foot-operated, multi-lock
Stabilizer Bar	Yes

BODY / CHASSIS

Frame Chassis	Aluminum I-beam
Front Body	ABS with Solarcoat
Rear Body	ArmorFlex®
Tires	20 x 10-8, 4-ply rated, All-trail II
Instrumentation	Electronic fuel gauge/hour meter, low-oil warning light
Trailer Hitch	Optional
Light Package	Headlights only package

DIMENSIONS

Cargo Bed Size	27.5 x 43.5 x 11 in (65 x 111 x 28 cm)
Bed Capacity	300 lb (136.1 kg)
Total Vehicle Capacity	800 lb (363.2 kg)
Seating Capacity	2 (with Cargo Box) or 4 (with Fixed Rear Seat)
Overall L x W x H	100.5 x 49.5 x 48 in. (255 x 126 x 122 cm)
Wheelbase	65 in (165 cm)
Ground Clearance	5.5 in (14 cm)
Fuel Tank Capacity	7 gal (26L)
Tread (Front/Rear)	34 / 38 in (86.4 / 96.5 cm)
Dry Weight (No Batteries or Fuel)	805 lb (365 kg)
Turning Radius	8.75 ft (2.7 m)
Speed Range	17-19 mph (27.4-30.6 kph)
Vehicle Warranty	2-year limited consumer; 1-year limited commercial

Vehicle shown with optional trailer hitch, tube bumper, and nerf bars.