



## PROPOSAL



# Carryall 295 Diesel

### FEATURES & BENEFITS

- 20 hp liquid-cooled Kubota engine
- Exclusive IntelliTrak™ automatic, full-time, 4-wheel drive system
- Certified Roll Over Protective Structure (ROPS) meets 5 different international standards
- 4-wheel hydraulic disc brakes
- Retractable seat belts
- Rustproof aircraft grade aluminum frame, chassis & cargo box
- 1,200 lb (544.3 kg) total vehicle capacity; Heavy-duty option 1,450 lb (657.7 kg)
- Dash features automotive design with glovebox, cupholders, storage spaces and tilt steering wheel.
- Headlights
- Our suspension enhances comfort a ride, reduces tire wear
- Heavy-duty steel tilt cargo box with flip-down tailgate
- Bucket or bench seat options
- Industry's Best 2-year Limited Warranty

### POWER SOURCE

|  |   |
|--|---|
| <b>Engine</b>                          | Kubota® D722, 719 cc, 3-cylinder, liquid-cooled |
| <b>Lubrication and Oil Filter Type</b> | Full-pressure, spin-on                          |
| <b>Maximum Torque</b>                  | 33 ft-lb (44.7 Nm)                              |
| <b>Horsepower</b>                      | 20 hp (14.9 kw)                                 |
| <b>Ignition</b>                        | Compression                                     |
| <b>4WD Engagement (Front/Rear)</b>     | IntelliTrak (Automatic / Auto locking)          |
| <b>Torque Converter</b>                | CVT   |
| <b>Electrical System</b>               | 12-volt, 500 CCA                                |

### STEERING / SUSPENSION

|                         |   |
|-------------------------|---|
| <b>Steering</b>         | Rack and pinion                                 |
| <b>Front Suspension</b> | Independent double A-arms with coil-over shocks |
| <b>Rear Suspension</b>  | Swing arm with coil-over shocks                 |
| <b>Brakes</b>           | 4-wheel, hydraulic disc                         |
| <b>Park Brake</b>       | Automotive style                                |

### BODY / CHASSIS

|                        |  |
|------------------------|--|
| <b>Frame Chassis</b>   | Tubular aluminum   |
| <b>Front Body</b>      | GE Gelyo high-impact, scratch-resistant, injection molded color                          |
| <b>Rear Body</b>       | All aluminum   |
| <b>Tires</b>           | All-terrain, 25 x 10.5-12, 4-ply   |
| <b>Instrumentation</b> | Electronic fuel gauge/hour meter, low oil warning light, coolant high temp warning light |
| <b>Light Package</b>   | Headlights   |

### DIMENSIONS

|                                      |   |
|--------------------------------------|---|
| <b>Flat Bed Size</b>                 | 48.8 x 49.8 x 10.9 in (124 x 126.5 x 27.7 cm)       |
| <b>Bed Capacity</b>                  | 800 lb (363.2 kg); Heavy-duty 1,050 lb (476.3 kg)   |
| <b>Total Vehicle Capacity</b>        | 1,200 lb (544.3 kg); Heavy-duty 1,450 lb (657.7 kg) |
| <b>Overall L x W x H</b>             | 124.6 x 60.0 x 78.6 in (316.5 x 152.4 x 199.6 cm)   |
| <b>Wheelbase</b>                     | 88.7 in (225.3 cm)                                  |
| <b>Differential Ground Clearance</b> | 7.4 in (18.8 cm)                                    |
| <b>Platform Ground Clearance</b>     | 12.1 in (30.7 cm)                                   |
| <b>Fuel Tank Capacity</b>            | 6.5 gallons (24.6 L)                                |
| <b>Tread (Front/Rear)</b>            | 48.8 in (124 cm)                                    |
| <b>Dry Weight</b>                    | 1,475 lbs (669.1 kg)                                |
| <b>Turning Radius</b>                | 13 ft (3.8 m)                                       |
| <b>Maximum Speed</b>                 | 25 mph (40.2 kph)                                   |
| <b>Vehicle Warranty</b>              | 2-year/2,000 hour limited                           |