

PROPOSAL



Carryall 295 Gas

FEATURES & BENEFITS

- 20.1 hp air-cooled Kawasaki® engine
- Exclusive IntelliTrak™ automatic, full-time, 4-wheel drive system
- Certified Roll Over Protective Structure (ROPS) meets 5 different international standards
- 4-wheel hydraulic disc brakes
- · Retractable seat belts

Turning Radius

Maximum Speed

Vehicle Warranty

- Rustproof aircraft grade aluminum frame, chassis & cargo box
- 1,200 lb (544.3 kg) total vehicle capacity; Heavy-duty option 1,450 lb (657.7 kg)
- Dash features automotive design with glovebox, cupholders, storage spaces and tilt steering wheel.
- Headlights
- Our suspension enhances comfort and ride, reduces tire wear
- Heavy-duty steel tilt cargo box with flip-down tailgate
- · Bucket or bench seat options
- Industry's Best 2-year Limited Warranty

POWER SOURCE		
Engine	Kawasaki 4-cycle, OHV, 675 cc, twin-cylinder industrial grade, air-cooled	
Lubrication and Oil Filter Type	Full-pressure, spin-on	
Maximum Torque	39.8 ft-lb (54.9 Nm)	
Horsepower	20.1 hp (17.2 kw)	
Ignition	Transistorized magneto	
4WD Engagement (Front/Rear)	IntelliTrak (Automatic / Auto locking)	
Torque Converter	CVT	
Electrical System	12-volt_500 CCA	

Torque Converter	CVT	
Electrical System	12-volt, 500 CCA	
STEERING / SUSPENSION		
Steering	Rack and pinion	
Front Suspension	Independent double A-arms with coil-over shocks	
Rear Suspension	Swing arm with coil-over shocks	
Brakes	4-wheel, hydraulic disc	
Park Brake	Automotive style	
	BODY / CHASSIS	
Frame Chassis	Tubular aluminum	
Front Body	GE Geloy high-impact, scratch-resistant, injection molded color	
Rear Body	All aluminum	
Tires	All-terrain, 25 x 10.5-12, 4-ply	
Instrumentation	Electronic fuel gauge/hour meter, low oil warning light	
Light Package	Headlights	
	DIMENSIONS	
Flat Bed Size	48.8 x 49.8 x 10.9 in (124 x 126.5 x 27.7 cm)	
Bed Capacity	800 lb (363.2 kg); Heavy-duty 1,050 lb (476.3 kg)	
Total Vehicle Capacity	1,200 lb (544.3 kg); Heavy-duty 1,450 lb (657.7 kg)	
Overall L x W x H	124.6 x 60.0 x 78.6 in (316.5 x 152.4 x 199.6 cm)	
Wheelbase	88.7 in (225.3 cm)	
Differential Ground Clearance	7.4 in (18.8 cm)	
Platform Ground Clearance	12.1 in (30.7 cm)	
Fuel Tank Capacity	6.5 gallons (24.6 L)	
Tread (Front/Rear)	48.8 in (124 cm)	
Dry Weight	1,339 lb (599 kg)	

13 ft (3.8 m)

25 mph (40.2 kph)

2-year/2,000 hour limited

