

## **PROPOSAL**



## Carryall 295SE Gas

## **FEATURES & BENEFITS**

- 20.1 hp air-cooled Kawasaki® engine
- Exclusive IntelliTrak<sup>™</sup> automatic, full-time, 4-wheel drive system
- Certified Roll Over Protective Structure (ROPS) meets 5 different international standards
- 4-wheel hydraulic disc brakes
- · Retractable seat belts

- Rustproof aircraft grade aluminum frame, chassis & cargo box
- 1200 lb (544.3 kg) total vehicle capacity; Heavy-duty option 1450 lb (657.7 kg)
- Dash features automotive design with glove box, cup holders, storage spaces and tilt steering wheel
- Our suspension enhances comfort and ride, reduces tire wear
- Heavy-duty steel tilt cargo box with flip-down tailgate
- Up to 4 passengers with bucket or bench seat options
- Industry's Best 2-year Limited Warranty

POWER SOURCE		
Engine	Kawasaki 4-cycle, OHV, 675 cc, twin-cylinder industrial grade, air-cooled	
Lubrication and Oil Filter Type	Full-pressure, spin-on	
Maximum Torque	39.8 ft-lb (54.9 Nm)	
Horsepower	20.1 hp (17.2 kw)	
Ignition	Transistorized magneto	
4WD Engagement (Front/Rear)	IntelliTrak (Automatic / Auto locking)	
Torque Converter	CVT	
Electrical System	12-volt, 500 CCA	

4WD Engagement (Front/Rear)	IntelliTrak (Automatic / Auto locking)
Torque Converter	CVT
Electrical System	12-volt, 500 CCA
	STEERING / SUSPENSION
Steering	Rack and pinion
Front Suspension	Independent double A-arms with coil-over shocks
Rear Suspension	Swing arm with coil-over shocks
Brakes	4-wheel, hydraulic disc
Park Brake	Automotive style
	BODY / CHASSIS
Frame Chassis	Tubular aluminum
Front Body	GE Geloy high-impact, scratch-resistant, injection molded color
Rear Body	All aluminum
Tires	All-terrain, 25 x 10.5-12, 4-ply
Instrumentation	Electronic fuel gauge/hour meter, low oil warning light
Light Package	Headlights
	DIMENSIONS
Flat Bed Size	48.8 x 49.8 x 10.9 in (124 x 126.5 x 27.7 cm)
Bed Capacity	800 lb (363.2 kg)
Total Vehicle Capacity	1600 lb (725.8 kg)
Overall L x W x H	157.6 x 60.0 x 78.6 in (400.3 x 152.4 x 199.6 cm)
Wheelbase	114 in (225.3 cm)
Differential Ground Clearance	7.4 in (18.8 cm)
Platform Ground Clearance	12.1 in (30.7 cm)
Fuel Tank Capacity	6.5 gallons (24.6 L)
Tread (Front/Rear)	48.8 in (124 cm)
Dry Weight	1786 lb (810.1 kg)
Turning Radius	17 ft (5.4 m)
Maximum Speed	25 mph (40.2 kph)
Vehicle Warranty	2-year/2,000 hour limited

