



PROPOSAL



Villager 6 Gas

FEATURES & BENEFITS

- 351 cc gasoline 10.4 hp engine
- Rustproof aircraft grade aluminum frame
- Independent front suspension with self-adjusting rack and pinion steering
- Carries up to 6 passengers
- Max speed of 16 mph (25.7 kph)
- Fixed Rear Seat Standard, Fold Down Rear Seat Available
- Taillights, Brake Lights, Halogen Headlights, and Horn
- Dual Dash Compartments
- Fuel gauge/hour meter standard
- ArmorFlex® Front Body for fade-resistant color
- Industry's Best 2-year limited warranty

POWER SOURCE	
Engine	Kawasaki 4-cycle, OHV, 351 cc, single-cylinder, air-cooled, pressure-lubricated, spin-on oil filter
Horsepower	10.4 hp @ 3,600 rpm, exceeds SAE J1940 Performance Standards
Governor	Automatic ground speed sensing
Governed RPM	2875 +/- 30
Drive Unit	Unitized transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse
Battery	112-volt, 500 CCA 85 min reserve
STEERING / SUSPENSION	
Steering	Self-adjusting rack & pinion
Suspension	Mono-leaf springs with dual hydraulic shocks
Brakes	Rear-wheel, mechanical drum
Park Brake	Foot-operated, multi-lock
Stabilizer Bar	Yes
BODY / CHASSIS	
Frame Chassis	Aluminum box beam with composite cross member
Front Body	Formion®
Body Color	Molded-in color
Tires	18 x 8.50-8, 4-ply rated, premium tread
Instrumentation	Electronic fuel gauge/hour meter, low-oil warning light
DIMENSIONS	
Total Vehicle Capacity	1500 lb (681 kg)
Seating Capacity	6
Overall L x W x H	124.0 x 47.3 x 48.0 in (315.0 x 120.1 x 121.9 cm)
Wheelbase	98.5 in (250.2 cm)
Ground Clearance	4.5 in (11.4 cm)
Fuel Tank Capacity	7 gal (26L)
Tread (Front/Rear)	34.5 in/38.6 in (87.6 cm/97.8 cm)
Dry Weight	745 lb (338.2 kg)
Outside Radius Circle	24.7 ft (7.5 m) dia
Turning Radius	12 ft (3.7 m)
Intersecting Aisle Radius	7.5 ft (228.6 cm)
Speed Range	14-16 mph (22.5-25.7 kph)