



PROPOSAL



Villager 8 Gas

FEATURES & BENEFITS

- 351 cc gasoline 11.5 hp engine
- Rustproof aircraft grade aluminum frame
- Independent front suspension with self-adjusting rack and pinion steering
- Carries up to 8 passengers
- Fixed Rear Seat Standard, Fold Down Rear Seat Available
- Taillights, Brake Lights, Halogen Headlights, and Horn
- Dual dash compartments
- Maximum speed of 16 mph (25.7 kph)
- ArmorFlex® front body for fade-resistant color
- Industry's Best 2-year limited warranty

POWER SOURCE	
Engine	Kawasaki 4-cycle, OHV, 351 cc, single-cylinder, air-cooled, pressure-lubricated, spin-on oil filter
Horsepower	11.5 hp @ 3,600 rpm, exceeds SAE J1940 Performance Standards
Governor	Automatic ground speed sensing
Governed RPM	2875 +/- 30
Drive Unit	Unitized transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse
Battery	112-volt, 500 CCA 85 min reserve
STEERING / SUSPENSION	
Steering	Self-adjusting rack & pinion
Front Suspension	Independent leaf spring with dual hydraulic shocks
Rear Suspension	Leaf springs with dual hydraulic shocks
Brakes	4-wheel mechanical drum
Park Brake	Foot-operated, multi-lock
Stabilizer Bar	Yes
BODY / CHASSIS	
Frame Chassis	Aluminum I-beam
Front Body	ArmorFlex®
Body Color	Matching paint over molded in color
Tires	18 x 6.50-8, 6-ply rated, premium tread
Light Package	Standard
Instrumentation	Electronic fuel gauge/hour meter, low-oil warning light
DIMENSIONS	
Total Vehicle Capacity	1500 lb (681 kg)
Seating Capacity	8
Overall L x W x H	157.0 x 47.3 x 48.0 in (398.8 x 120.1 x 121.9 cm)
Wheelbase	131.5 in (334 cm)
Ground Clearance	4.5 in (11.4 cm)
Fuel Tank Capacity	7 gal (26L)
Tread (Front/Rear)	34.5 in/38.6 in (87.6 cm/97.8 cm)
Dry Weight	866 lb (393.2 kg)
Outside Radius Circle	32.6 ft (9.9 m) dia
Turning Radius	15.9 ft (4.8 m)
Intersecting Aisle Radius	9 ft (274.3 cm)
Speed Range	14-16 mph (22.5-25.7 kph)
Vehicle Warranty	2-year, limited; 4-year limited battery