

Specifications

1550, 1550 SE
Gasoline

1550, 1550 SE, 1550 with IntelliTrak
Diesel

Engine	Kawasaki® 4-cycle OHV, 675 cc, twin-cylinder industrial grade	Kubota® 719 cc, 3-cylinder industrial grade
Engine — Cooling	Air	Liquid
Engine — Lubrication & Oil Filter Type	Full-pressure, spin-on	Full-pressure, spin-on
Max Torque	39.8 ft-lb (54.0Nm) @ 2,400 rpm	32.5 ft-lb (44.1 Nm) @ 2,600 rpm
Horsepower	23.0 hp (17.2 kw) @ 3,600 rpm per SAE J1940/1349	20 hp (14.9kW) @ 3,600 rpm per SAE J1940/1349
4WD System Type	Automatic – IntelliTrak All-Wheel-Drive	Automatic – IntelliTrak All-Wheel-Drive
Differential — Front	Automatic – IntelliTrak All-Wheel-Drive	Automatic – IntelliTrak All-Wheel-Drive
Differential — Rear	Auto locking – IntelliTrak All-Wheel-Drive	Auto locking – IntelliTrak All-Wheel-Drive
High-Low Range Engagement	Automatic – IntelliTrak All-Wheel-Drive	Automatic – IntelliTrak All-Wheel-Drive
Electrical System	12-volt, 500 CCA	12-volt, 500 CCA
Torque Converter	CVT	CVT
Steering Type	Rack & pinion	Rack & pinion
Tilt Steering Wheel	Standard	Standard
Adjustable Driver's Seat	Standard	Standard
Suspension — Front	Independent double A-arms w/coil-over shocks	Independent double A-arms w/coil-over shocks
Suspension — Rear	Swing arm w/coil-over shocks	Swing arm w/coil-over shocks
Brakes	4-wheel, hydraulic disc	4-wheel, hydraulic disc
Park Brake	Foot-operated	Foot-operated
Frame/Chassis	6061 Aircraft-grade tubular aluminum	6061 Aircraft-grade tubular aluminum
Body — Front	High-impact, scratch-resistant, GE Geloy injection molded color	High-impact, scratch-resistant, GE Geloy injection molded color
Body — Rear	Rugged, scratch-resistant injection molded plastic	Rugged, scratch-resistant injection molded plastic
Tires — Front/Rear	Mud, 25 x 11-12, 4-ply (optional all-terrain tires available)	Mud, 25 x 11-12, 4-ply (optional all-terrain tires available)
Instrumentation	Electronic fuel gauge/hour meter, low-oil warning light (speedometer optional)	Electronic fuel gauge/hour meter, low-oil warning light, coolant high-temp warning light (speedometer optional)
Bed Length x Width x Height	48" x 49.8" x 10.9" (121.9 x 126.5 x 27.7 cm)	48" x 49.8" x 10.9" (121.9 x 126.5 x 27.7 cm)
Overall Bed Height	33" (83.8 cm)	33" (83.8 cm)
Bed Load Capacity	800 lb (362.9 kg) standard (1,050 lb [476.3 kg] available 1550 only)	800 lb (362.9 kg) standard (1,050 lb [476.3 kg] available 1550 only)
Total Vehicle Capacity	1550: 1,200 lb (544.3 kg) standard (1,450 lb [657.7 kg] available) 1550 SE: 1,600 lb (725.8 kg)	1550: 1,200 lb (544.3 kg) standard (1,450 lb [657.7 kg] available) 1550 SE: 1,600 lb (725.8 kg) 1550 with IntelliTrak: 1,200 lb (544.3 kg)
Fuel Tank Capacity	6.5 gallons (24.6 Liters)	6.5 gallons (24.6 Liters)
Overall Length x Width x Height	1550: 124.6" x 60" x 78.6" (316.5 x 152.4 x 199.6 cm) 1550 SE: 157.6" x 60" x 78.6" (400.3 x 152.4 x 199.6 cm)	1550: 124.6" x 60" x 78.6" (316.5 x 152.4 x 199.6 cm) 1550 SE: 157.6" x 60" x 78.6" (400.3 x 152.4 x 199.6 cm) 1550 with IntelliTrak: 148.6" x 60" x 78.6" (377.4 x 152.4 x 199.6 cm)
Wheelbase	1550: 81.5" (207 cm) 1550 SE: 114" (289.6 cm)	1550: 81.5" (207 cm) 1550 SE: 114" (289.6 cm) 1550 with IntelliTrak: 81.5" (207 cm)
Ground Clearance — Differential	7.4" (18.8 cm)	7.4" (18.8 cm)
Floor Ground Clearance	12.1" (30.7 cm)	12.1" (30.7 cm)
Dry Weight — Less Batteries	1550: 1,430 lb (648.6 kg) 1550 SE: 1,605 lb (728 kg)	1550: 1,559 lb (707.2 kg) 1550 SE: 1,786 lb (810.1 kg) 1550 with IntelliTrak: 1,709 lb (775.2)
Turning Radius	1550: 13 ft (3.9 m) 1550 SE: 17.7 ft (5.4 m)	1550: 13 ft (3.9 m) 1550 SE: 17.7 ft (5.4 m) 1550 with IntelliTrak: 13.8 ft (4.2 m)
Vehicle Warranty	2-year/2,000 hour, limited	2-year/2,000 hour, limited

DESIGN

STRENGTH

AGILITY

POWER