


## JUST LOOK AT THESE BENEFITS!

- Rustproof twin I-beam welded aluminum frame for long life and good resale value
- Your choice of an 11.5 hp (8.6 kW) Kawasaki gasoline engine or a 48-volt electric system with six 8-volt PowerDrive Batteries
- Your choice of a fixed aluminum cargo box or a fold-down rear-facing, two-passenger seat that converts into a carrying bed
- A deluxe brush guard and stout bumper to protect the body as well as a rear differential guard, all at no additional charge
- A spacious bench seat with ample leg room as well as cup holders and a sport steering wheel for added comfort
- A 7 gal (27 L) fuel tank for hours of driving pleasure

- 22 in (559 mm) tires for driving on the beach or off road
- Safety features such as halogen headlights and reverse warning indicator
- 48-volt, 13-amp battery charger and low-battery warning light (electric model)
- A great selection of options and accessories, including a canopy top, windshield, fold-down rear seat and custom colors
- A two-year consumer warranty, the best in the industry

## AVAILABLE COLORS



FIND YOUR 	<b>XRT 850</b>	
	<b>4X2 ELECTRIC</b>	<b>4X2 GAS</b>
	Standard features include a powerhouse 48-volt electric system, 22 in (559 mm) tires for beach or off-road driving, deluxe brush guard, rear differential guard and a fixed aluminum cargo box or fold-down seat.	
	Standard features include a lean-&-mean 11.5 hp (8.6 kW) Kawasaki gas engine, 7 gal (27 L) gas tank, 22 in (559 mm) tires, deluxe brush guard, rear differential guard and a fixed aluminum cargo box or rear-facing 2-passenger seat.	
Drive Motor	3.2 hp (2.4 kW) continuous / 10 hp (7.5 kW) intermittent	NA
Engine	NA	11.5 hp (8.6 kW) @ 3600 rpm per SAE J 1940/1349
Electrical System	48-volt DC, reduced-speed reverse	12-volt, 500 cca
Steering	Self-adjusting rack and pinion	
Suspension	Front and rear tapered mono-leaf springs with dual hydraulic shocks	
Brakes	Dual rear wheel self-adjusting with cast-iron drums, single brake pedal and automatic-release park brake	
Frame Chassis	Twin I-beam welded aluminum	
Tires	22 x 11 - 10 in (559 x 279 - 254 mm) tubeless, six-ply rated	
Instrumentation	Low battery warning light	Fuel gauge / Hour meter / Low oil warning light
Seating Capacity	Two / Optional four	
Overall L x W x H	110 x 51 x 52 in (280 x 129 x 132 cm)	
Wheelbase	67 in (171 cm)	
Ground Clearance	6 in (16 cm)	
Front Tread	39 in (100 cm)	
Rear Tread	41 in (104 cm)	
Dry Weight (no Batteries or Fuel)	1022 lb (464 kg)	938 lb (425 kg)
Vehicle Rated Capacity	800 lb (363 kg)	
Fuel Tank	NA	7 gal (27 L)
Forward Speed	16 mph (26 kph)	



©2012 Club Car LLC. Club Car believes the information and specifications in this piece of literature were correct at the time of printing. Specifications, standard features, options, fabrics and colors are subject to change without notice. Some features may be unavailable when your vehicle is built. Some vehicles are pictured with options that may be available at extra cost or may not be available on some models. Ask your dealer about the availability of options and verify that the vehicle you ordered includes the equipment you ordered. There are no warranties, expressed or implied, contained herein. See the Limited Warranty in the owner's manual or write to: Club Car, PO Box 204658, Augusta, GA 30917. The company reserves the right to make design changes without obligation to make these changes on previously sold units or systems.

CCN 18040014 Rev 05/12

1.800.CLUBCAR WWW.CLUBCAR.COM